



PERFECT INSULATION

Safe for years.

Guaranteed Uw below 0,79W/m²K for reference window – the lower, the warmer!











single-family housing.

Our passive windows ensure:

✓ thicker profile sections with more chambers,

Choose windows with the best possible performance

on the market. Designed for very demanding, modern

- ✓ solid triple glazing,
- consistent low thermal permeability.

Significant noise reduction and reduction of heat loss up to 30%.



V82 POWERTHERM +

- Seven-chambers A class profile Our best of the best passive windows, designed for demanding, modern single-family housing.
- Perfect parameters
 An additional 3rd seal
 ensures an exceptionally
 low heat transfer coefficient.
 That all enclosed in a well
 designed, classic profile.
- Extra accessories without any additional payment. Warm Swisspacer and Maco Soul handle with lock of the faulty position.



KÖMMERLING 88

- The 88 premium window system.
 The seven-chamber system with
 - a depth of 88 mm with a central gasket offers passive windows as standard.
- Extras included.

Insulating wedge, warm edge spacer, triple-glazed unit, modern handle and a lot of veneer variants to choose from.

Wide glazing options.

The modern design allows for the placement of glazing units up to 56 mm with the possibility of embedding a triple-glazed unit or special functional glazing.



PK76 INNOVO +

- Six-chambers Class B system An elegant, classic profile with a depth of 76 mm.
- The highest quality guarantee Additional 3rd seal and the best parameters of thermal insulation. Uw for the reference window reaches the value of 0,73 W/m²K.
- One system. Many advantages Modern quality through functionality, statics, appearance, thermal and acoustic insulation coefficients.



WITRAŻ HS82

- Hidden gaskets Protection against draft, dust and rain.
- Compatibility It does not take up space nside and allows you to enjoy the light of day.
- Optionality

The low threshold does not satisfy you?
We like challenges.
We will use a high threshold especially for you.

CLASSICALLY FOR EVERYONE

Classic does not mean boring.

Create a beautiful space where you feel safe.











Windows resistant to changing climatic conditions. and extremely easy to clean.

Our windows provide:

- √ very good thermal insulation,
- √ home security,
- universal design.

The optimal choice for many years.



PK76 INNOVO

- A five-chamber class B system An elegant, classic profile with a depth of 76 mm.
- Protection

Thanks to the perfect acoustic insulation, the house is much quieter, and the installation of anti-burglary systems increases safety.

A wide range of colors In addition to white, we offer a wide range of veneer colors.



V70 PERFECTLINE

Class A quality

The five-chamber profile 70 mm, colored for the veneer color provides an aesthetic look of the frame after many years of use.

Good form

Thick walls of the profiles provide excellent window statics, even with daily temperature fluctuations from -2 to 16°C.

Guarantee of security Robust Maco Multimatic fittings ensure safety.



PN70 BALANCE

For a changing climate

The basic and universal version of the profile with a depth of 70 mm.

Excellent tightness

Modern gaskets perfectly protect against draft, dust and rain.

Easy care

The outer surface is extremely resistant to changing weather conditions.



PREMISLIDE 76+

Large and small sliding structures.

The minimum leaf size is only 52 x 61 cm.

High tightness.

Thanks to properly matched sash gaskets, which are pressed against the frame along the entire perimeter, PremiSlide 76+ achieves very good parameters in terms of air permeability, water tightness and resistance to wind pressure.

Optional SOFT CLOSE.

It is a completely hidden mechanism that slows down the sash movement in the final phase of closing.

It is possible to use a triple-glazing with a width of 42 mm. Then Uw can be even 0,79 W/m²K.

TROCAL

COLOR PALETTE









52 Walnut



WI Winchester XA



38



CQ

GD Quartz grey

grey Ю Irish Oak

UD Anthrazite grey



Chocolate brown

15

Dark oak

Dark green



Mountain pine

Moss green 37



42 Macore

44 Wine red





58































QB Quartz grey SFTN mat










WX White

Turner Oak malt

VEKA













































































3069037

Douglas



aluminum 701205083






















Black brown



915205001

PROFILE	V70 PERFECTLINE	V70 SWINGLINE	V82 POWERTHERM+	PN70 BALANCE	PK76 INNOVO	PK76 INNOVO+	KÖMMERLING 88
profile class	Α	Α	А	В	В	В	В
number of chambers in the frame	5	5	7	5	5	6	7
installation depth	70 mm	70 mm	82 mm	70 mm	76 mm	76 mm	88 mm
thickness of the profile walls	3 mm	3 mm	3 mm	2,7 mm	2,7 mm	2,7 mm	2,7 mm
number of seals on the perimeter	2	2	3	2	2	3	3
type of seals in the profiles	EDPM	EDPM	EDPM	EDPM	EDPM	EDPM	EDPM
color of the seal in white windows	black	black	black	grey	grey	grey	grey
Uw value for the reference window 1.23m x 1.48m from	1,1 W/m²K	1,1 W/m²K	0,74 W/m²K	0,79 W/m²K	0,76 W/m²K	0,73 W/m²K	0,71 W/m²K
Uf value from	≥ 1,4	≥ 1,4	≥1	≥ 1,2	≥1,1	≥1	≥ 0,93
steel standard	frame sash fixed mullion	n frame sash fixed mullion	n frame sash fixed mullion	frame sash fixed mullion	frame sash fixed mullion	frame sash fixed mullion	frame sash fixed mullion
variant I.	1,25 1,5 1,5 mm mm	1,25 1,5 mm mm	1,25 1,5 mm mm	1,5 1,5 mm	1,5 1,5 mm 1,5mm	1,5 1,5 mm 1,5mm	1,5 1,5 1,5 mm 1,5mm
reinforced steel:	frame sash fixed mullion	frame sash fixed mullion	n frame sash fixed mullion	frame sash fixed mullion	frame sash fixed mullion	frame sash fixed mullion	frame sash fixed mullion
variant II.	1,5 1,75 1,5 mm mm	1,5 mm nm	1,5 mm 1,75 mm	2,0 mm 2,0 1,5mm	2,0 2,0 1,5mm	2,0 2,0 1,5mm	1,5 mm 2,0 1,5mm
variant III.				2.0 2,5 1,5mm	2,0 2,5 1,5mm	2,0 2,5 1,5mm	1,5 mm 2,5 1,5mm
variant IV.				1,5 1,5 1,5mm mm 1,5mm	1,5 mm 1,5mm 1,5mm	1,5 1,5 1,5mm mm	1,5 1,5 1,5mm 1,5mm
variant V.				1,5 2,5 2 mm	1,5 2,5 mm 2,5	1,5 2,5 2 mm	1,5 2,5 2 mm mm
glazing bead (standard glazing package)	straight	round / straight for packages> 36mm	straight	straight	straight	straight	straight
type of glazing package	24 mm	24 mm	48 mm	24 mm	48 mm	48 mm	48 mm
possibility of inserting a glazing package	24-40 mm	24-40 mm	24-48 mm	24-42 mm	24-48 mm	24-48 mm	44-56 mm
spacer frame	aluminium	aluminium	warm TGI	aluminium	aluminium	aluminium	warm TGI
resistance to wind loads - frame deflection	C2/B4	C2/B4	C2/B2	C5/B5 for single-sash windows C3/B3 multi-sash windows C1/B2 for balcony multi-sash windows	C5/B5	C5/B5	C4/B5 for single-sash windows C1/B2 for windows with flying mullion
water resistance	5A	5A	9A	9A	9A	9A	9A
air permeability	4	4	4	4	4	4	4
anti-theft catches / 1 sash	1	1	1	1	1	1	1
micro-ventilation in the tilt and turn sash	. <	<	<	<	. <	<	<
incorrect tilting lock	<	<	<	<	<	<	<
seal of the catch-notch in the frame	<	<	<	<	<	<	<
handle	standard aluminium	standard aluminium	Square	standard aluminium	standard aluminium	standard aluminium	Hoppe Secustic
transport handles	< <	< <	< <	< <	< <	< <	< <
warranty period for rectangular windows		5 years (applies to fixed w	5 years (applies to fixed windows or with multi-point locking fittings	in the	urn, turn or tilt)		
Possibility of manufacturing:							
patio door option	∀	×	✓	V	٧	V	V
external door option	<	×	<	<	<	×	×
option of a window with a window sash with a 2-sided handle and the PZ25 lock	<	×	×	×	<	×	×
option of a window with an intermediate sash, a 2-sided handle and a PZ35 lock	. <	×	×	×	×	×	×
PSK tilt and slide window option	< <	< <	<	< <	<	<	< <
HS lift and slide window option	<	X	<	×	<	<	×



WITRAŻ **FAMILY BUSINESS**



WITRAZ is a family-owned company existing on the market since 1999, boasting the largest PVC producer in the north-eastern region of Poland. We are one of the few companies in the country producing three materials - PVC, wood and aluminum.

We have the latest technological solutions, the most automated production line, allowing for the production of 250,000 PVC windows per year. Nevertheless, we do not mass produce windows. We approach each order very individually, we take care of every detail, at every stage of implementation. From comprehensive advisory services, through specialized production on the most advanced production line, to meticulous control and safe preparation for transport. We are characterized by an excellent design oriented on changing conditions throughout Europe.

We want to show every client that the window can not only be of high quality, but above all functional and simply beautiful.

PVC ALUMINIUM WOOD-ALU WOOD

Germany • Italy • Lithuania • USA • Scandinavia • Morocco We export to: Switzerland • Latvia • Norway • France • Israel • Sweden Belgium • Estonia • Austria • Japan • Hungary • United • Czech Kingdom Republic

























